



# **JZ-PT350**























#### Main Feature


#### Colorful LED indicators

Status LED	Specification	
White	Printer Power On	
Green	Printer is ready in idle condition	
Red	Wrong Status (Out of paper,cover open, and so on)	
Rose Pink	Paper near end and printer is in normal	
Blue	Printer is busy	









With cutter jam auto eliminating design, only flip up the front cover of JZ-PT350, it will relieve you from cutter jam instanly



### Plug-in connected port

plug-in connected port design, Multi interfaces can be interchanged quickly





## **Specification**

JZ-PT350

ITEM		PARAMETER
Printing	Printing method	Direct thermal printing
	Resolution	203dpi
	Printing width	72mm
	Printing speed	Max.300mm/s
	Printing density	Adjustable from degree 1 to degree 4
Page mode		YES
Memory	RAM	1Mb
Memory	Flash	4Mb
Character Set	Font	Font A:12*24, Font B 9*17 CHN:24*24
	Alphanumeric	95
	Expanded character	128*30
	International character	15
Graphics		Support bitmap with different density and user defined bitmap
Grapinos		(64K for per bitmap, and 256K for total)
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
Dairoon Dairo	2D	PDF417, QR code(DataMatrix/Maxicode/Azec optional)
Interface		Default:USB,drawer Optional:Parallel,WiF,RS232,Ethernet,Bluetoothi
Detection	Sensor	Paper out, paper near end, and paper jam detection, cover open detection
Power supply	Input	AC100V-240V 50-60HZ
	Output	DC 24V±5%,2.0A,A-1009-3P interface
Paper	Paper type	Standard thermal paper
	Paper width	79.5±0.5mm/57.5±0.5mm
	Paper thickness	0.056~0.1mm
	Paper roll diameter	83mm Max.
	Paper loading	Easy loading
	Paper cutting	Auto cutting or manual cutting
Physical characteristics		5~45°C /10~95%RH
	Storage condition	-10~50°C /10~95%RH
	Dimension	191(L)*130(W)*131(H)mm
	N.W.	1.63kg (without paper roll)
Reliability	TPH life	150km
	Cutter life	2,000,000 times
	Motor life	50,000,000 lines
Firmware	Emulation	ESC/POS
Software	Driver	Windows 2000/ XP /Vista /7 /8 /POSReady Linux, OPOS

Authorized Reseller: